

UV乾燥系統

c sun 志聖

UV CURING EQUIPMENT

PCB專用

UVC-754M/904M

7.5KW/9KW x 4 pcs(M Lamp)



UVC-503W

5KW x 3 pcs(H Lamp)



UVC-754MD/906MD

Double Side

相關耗材



UV能量計
Power Map



紫外線量測表
EIT UV Meter



水冷毛細燈管
Capillary Lamp



UV水銀燈 金屬鹵素燈
Mercury, Metal Halide UV Lamp

Leading in Thermal and UV Light Processing Equipment

UV機規格：

適用於PCB線路印刷、防焊綠漆、文字油墨印刷後乾燥

Single Side UV - Available for Pattern Printing/Solder Mask/Legend Curing

型號 Model	UVC-753M	UVC-754M	UVC-903M	UVC-904M	UVC-503W
UV燈 UV lamp	鹵化金屬燈 7.5KWx3pcs metal halide	鹵化金屬燈 7.5KWx4pcs metal halide	鹵化金屬燈 9.0KWx3pcs metal halide	鹵化金屬燈 9.0KWx4pcs metal halide	水銀燈 5.0KWx3pcs mercury lamp
發光長/強度 Arc/Intensity	625mm 80w/120w/cm	625mm 80w/120w/cm	750mm 80w/120w/cm	750mm 80w/120w/cm	625mm 80w/cm
外尺寸 Exterior Diemension (WxDxHmm)	1200×2440×2325	1200×2440×2325	1200×2440×2325	1200×2150×2400	1020×2440×2075
輸送裝置 Conveyor	SUS力骨輸送網加鍊條 SUS mesh belt w/chain				SUS輸送網具 防偏裝置
冷卻方式 Cooling	強制氣冷式 Forced-air cooling				

雙面UV機規格：

適用於防焊綠漆

Double Side UV - Available For Solder Mask

型號 Model	UVC-504D	UVC-754MD	UVC-906MD
UV燈 UV lamp	水銀燈 5KWx4pcs mercury lamp	鹵化金屬燈 7.5KWx4pcs metal halide	鹵化金屬燈 9.0KWx6pcs Metal Halide
發光長/強度 Arc/Intensity	625mm 80w/cm	625mm 120w/cm	750mm 120w/cm
外尺寸 Exterior Diemension (WxDxHmm)	1300×2200×2305	1500×2800×2305	1480×2800×2414
輸送裝置 Conveyor	矽橡膠/鐵氟龍滾輪傳送 Silicon/Teflon roller		
冷卻方式 Cooling	強制氣冷式 Forced-air cooling		

Due to C SUN continuing efforts to improve their systems, these specifications are subject to change without notice.
受長期研發需要，本公司保有規格修改之權利，恕不另行通知

DM201106-1000

www.csun.com.tw

志聖總公司(台北廠)
新北市林口區工二工業區工八路2-1號
TEL:886-2-2601-7706
FAX:886-2-2603-4728

竹科分公司
竹科工業東九路7-2號3F
TEL:886-3-666-2883
FAX:886-3-666-2892

台中廠
台中市工業區10路17號
TEL:886-4-2359-1651
FAX:886-4-2350-1860

志聖科技(廣州)
廣州市花都区獅嶺鎮利和路6號
TEL:86-20-8684-6341-3
FAX:86-20-8691-0139

東莞分公司
東莞市長安鎮廈崗村
第一工業區崗砂路10號
TEL:86-769-8533-1146
FAX:86-769-8533-1145

昆山分公司
昆山市玉山鎮城北高科技
工業園志聖路36號
TEL:86-512-5778-0230
FAX:86-512-5778-0229