

無氧化烤箱

Inert Gas Oven



QMO-2DSF



QMO-4C

Oxygen-Free Process Results in
High-Curing Quality

Features :

- Chamber fully filled with inert gas (CO₂, N₂) to prevent material oxidation during operation.

- These ovens are used in industries such as IC packaging, LCD, Transistor, Rectifier, Diode, Quartz Oscillator, Hybrid circuits...



QHMO-2



機 種 Model	QHMO-2 (含氧量<50PPM)	QMO-2DSF(兩爐式) Dual Oven	QMO-4C(台車式) Cart Oven
內尺寸 Interior W/D/H mm	610×610×610	710×610×560	710×610×910
外尺寸 Exterior W/D/H mm	1450x1130x1212	1460×960×1790	1380×900×1390
電源 Power	220V 3 ϕ 60HZ 9KVA / 15KVA	220V 3 ϕ 60HZ 12KVA	220V 3 ϕ 60HZ 12KVA
溫度範圍 Temp. Range	+60°C~Max 300°C / +60°C~Max 500°C +60°C~250°C Max		
溫度控制 Temp. Controller	自動PID控制，電子感應，數字顯示 Digital Display and Automatic PID Control ±0.5%		
溫度系統 Control System	輸入用CA感應棒，輸出以SSR無接點 Input : CA Sensor Output : SSR		
溫度均勻度 Temp Uniformity	300°C ±1.5% 500°C ± 2%	at 175°C ±1% (空爐 No-load)	at 175°C ±1.25% (空爐 No-load)
昇溫時間 Rise Time	+60°C~300°C 45mins +60°C~500°C 70mins	+60°C~250°C 40mins	
進氣口 Inlet	N2 : 100s (3.5kgf/cm ²)	Air ϕ 8mm ,N2 ϕ 6mm	Air ϕ 10mm ,N2 ϕ 6mm
排氣口 Outlet	最大3/8"(爐內) 冷卻夾層排氣 ϕ 4"	ϕ 4" With Automatic Damper	
材質 Materials	內中桶SUS304日製陽極不鏽鋼板，外部SS41#鋼板烤漆 ■ Interior:Stainless Steel ■ Exterior:Steel with Baked Enamel ■ Rockwool Insulation		
電熱 Heater	覆套式電熱器 Sheathed Heater		
安全裝置 Safety Device	漏電斷路器，超溫防止保護裝置，電熱過電流保護裝置，馬達過熱電流保護， 機台異常蜂鳴器顯示，三相逆相防止器，控制按鍵加防觸蓋 ■ Leakage Circuit Breaker ■ Over Temperature Protection ■ For Heater Overload ■ Buzzer ■ Phase Reverse ■ For Motor Overload		
標準配件 Standard Parts	流量計，圓孔盤 Flow Meter SUS 304#Perforated Tray	流量計，電磁門扣，測試孔 圓孔盤，資料袋 Flow Meter, Electromagnetic Door Lock, SUS 304#Perforated Tray Test Hole	流量計，電磁門扣，測試孔 內桶底部不鏽鋼滾輪 Flow Meter, Electromagnetic Door Lock, SUS 304#Perforated Tray Test Hole
選購品 Option	可程式溫控器，記錄器，六點溫度顯示器，自動啓閉排風門，三色指示燈，台車及烘烤架 ■ Recorder ■ Programmable Temperature Controller ■ Automatic Damper ■ Light Tower ■ Cart Shelves		

Due to C SUN continuing efforts to improve their systems, these specifications are subject to change without notice.
因應長期研發需要，本公司保有規格修改之權利，恕不另行通知

DM201606-0000

業務洽詢專線： +86-139-26269713 (華南) +86-139-26260250 (華東) +886-935-227109 (臺灣)

jung@csun.com.tw

台北

新北市林口區工二工業區
工八路2-1號
TEL:886-2-26017706
FAX:886-2-26018854

台中

台中市南屯區
精科二路11號
TEL:886-4-23591651
FAX:886-4-23592678

廣州

廣州市花都區獅嶺鎮
利和路6號
TEL:86-20-86846341-3
FAX:86-20-86910139

東莞

東莞市大朗鎮長塘第三工業區78號
松湖雲谷雲松樓1樓
TEL:86-769-85331146
FAX:86-769-85331145

昆山

江蘇省昆山市高新區(玉山鎮)
恒盛路1369號
TEL:86-512-57780230
FAX:86-512-57780229